

MKF 2011 TS



Electric combi oven with touch screen 20 trays 1/1 GN

Plus

Patented fan guard system Airflowlogic™	
Patented system for direct steam Humilogic™	
Patented system for cooking chamber drying Drylogic™	
Available on request at the order	Voltage (V) : AC 220/230 3
	Left hinged opening door *
Humidity management software	
Wi-Fi communication system	
Knob for quick selection of the touch screen	
Programmable oven start	
N° 40 recipes stored	
Control panel in 42 languages: Arabic, Armenian, Azerbaijani, Bahasa (Indonesia), Bahasa (Malaysia), Bosnian, Bulgarian, Chinese, Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, Georgian, German, Greek, Hungarian, Icelandic, Italian, Japanese, Kazakh, Latvian, Lithuanian, Norwegian, Persian (Iran), Philippine, Polish, Portuguese, Romanian, Russian, Serbian, Slovenian, South Korean, Spanish, Swedish, Thai, Turkish, Ukrainian, Vietnamese	
HACCP system	
Adjustable door hinges	

Dimensional features

Dimensions (WxDxH mm)	930 x 1035 x 1900
Weight (kg)	247,2
Distance between rack rails (mm)	80

Electrical features

Power supply (kW)	31 (44 amps)
Frequency (Hz)	50/60
Voltage (V)	AC 380/400 3N
N° motors	4 bidirectional
Boiler (kW)	/
Protection against water	IPX5

Functional features

Power	Electricity
Capacity	N° 20 trays/grids 1/1 GN
Type of cooking	Semistatic + ventilated
Steam	Direct steam controlled by touch screen (10 levels)
Cooking chamber	AISI 304 stainless steel
Temperature	30 - 270 °C
Temperature control	2 Digital probes thermometer

The evolution of the species.

The most powerful oven in the MILLENNIAL line, equipped with 5 fans distributed in height to ensure uniform cooking to all your dishes.

Cook the first and second courses and side dishes together on the removable 20-tray trolley: the impeccable tightness of the cooking chamber is ensured by an ingenious exclusive patent.

Only with MILLENNIAL technology can you really feel free to cook large quantities, without sacrificing the attention to details needed to achieve a quality result.



Equipment

Cardboard box dimensions with pallet (WxDxH mm)	990 x 1090 x 2065 mm
USB port	
Multipoint core probe cod. MKSCMU	
Automatic washing system integrated	
Hinge with door locking for openings adjusted at 60°, 90°, 120°, 180°	
Trolley with removable handle and braked wheels cod. EKCR 20 TC	

Optionals

1/1 GN stainless steel 304 grid, for cooking ribs	KGC/A
Chromed grid 1/1 GN	KG9G
AISI 304 grid 1/1 GN	KG9GX
AISI 304 vertical cooking grid for 8 chicken 1/1 GN	KGP
AISI 304 Tray 1/1 GN	KT9G
Smooth plate with non-stick coating 1/1 GN	KPGL11A
Striped plate with non-stick coating 1/1 GN	KPGR11A
AISI 304 Perforated tray 1/1 GN for cooking nuggets	EKTF 11

